



LIFT ACCESS



Overview

I/O module can be connected to the Falco Controller through a Falco Interface Board as an extra Lift control output point. Each interface module has 8 Output provides eight contact closure outputs. This board has been design to be cascaded up to a maximum of 64 output points.

This board is intended for non-reader type applications where it is desirable to control Lift Access and home automation. This board also provides eight form-C type relay outputs, which can be used to control external equipment, such as lights, gate motors and normally used in Lift Access Control that can control up to 64-floor.

Specification

- Power Supply : 12VDC input (Internal/External)
- Output : 8 Output dry contact to drive external equipment (siren, motor, lift access, etc)
- Relay Output : 10A contact rating
- Current Consumption : 0.25A
- Dimensions : 20mm(H) x 65mm(W) x 185mm(D)
- Lift access control that can control the access for maximum of 64 floors.
- Home Automation control to control external devices such as air-corn, lights, etc.

Key Highlights

- Supports Automation Control up to a maximum of 64 devices.
- Supports Lift Access Control up to a maximum of 64 floors.

Order Information

1. For 1-8 Floor :
FALCO-8 SERIES-LIFT CTRL(3A)-PCB, FALCO-8 SERIES-INF, FALCO-8 SERIES-I/O
2. For 1-16 Floor :
FALCO-8 SERIES-LIFT CTRL(3A)-PCB, FALCO-8 SERIES-INF, FALCO-8 SERIES-I/O (2 pcs)
3. For 1-32 Floor :
FALCO-8 SERIES-LIFT CTRL(3A)-PCB, FALCO-8 SERIES-INF, FALCO-8 SERIES-I/O (4 pcs)
4. For 1-64 Floor :
FALCO-8 SERIES-LIFT CTRL(3A)-PCB, FALCO-8 SERIES-INF, FALCO-8 SERIES-I/O (8 pcs)

***Reader optional